



OnNix Hydraulic Oil HD 68

Material Safety Data Sheet

1. COMPOSITION/INFORMATION ON INGREDIENTS

Distillates (Petroleum),Hydrotreated Heavy Parafinic - CAS 64742-54-7 @ > 90%

The highly refined oil contains <3% (w/w) DMSO-extract, according to IP346.

2. HAZARDS IDENTIFICATION

Emergency Overview

Apperance and Odour	: Clear,Liquid at room temperature.Slight hydrocarbon.
Health Hazards	: High-Pressure injection under the skin may cause serious damage including local necrosis.
Safety Hazards	: Not classified as flammable but will burn at high temperature.
Environmental Hazards	: Not classified as dangerous for the environment.

Health Hazards	: Not expected to be a health hazard when used under normal conditions.
Health Hazards	: Under normal conditions of use, this is not expected to be a primary
Inhalation	route of exposure.
Skin Contact	: Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Contact	: May cause slight irritation to the eyes.
Ingestion	: Low toxicity if swallowed.
Other Information	: High-Pressure injection under the skin may cause serious damage including local necrosis. Used oil may contain harmful impurities.
Signs and Symptoms	: Oil acne/focolliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Local necrosis is evidenced by delayed onset of pain and tissues damage a few hours following injection. Ingestion may result in nausea, vomitting and/or diarrhoea.
Aggravated Medical Condition	: Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material : Skin.
Environmental Hazards	: Not classified as dangerous for the environment.
Additional Information	: Under normal conditions of use or in a foreseeable emergency, this product does not meet the definiton of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

3. FIRSTAID MEASURES

General Information	: Not expected to be a health hazard when used under normal conditions.
Inhalation	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.

Skin Contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing up with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
Eye Contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	: In general, no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician	: Treat symptomatically. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

4. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Flash point	: Typical 290 C / 554 F (COC)
Upper/Lower Flammability or Explosion limits	: Typical 1-10%(V)(based mineral oil)
Auto Ignition Temperature	: >320 C / 608 F
Specific Hazards	: Hazardous combustion products may include : A complex mixtures of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	: Do not use water in a jet.
Protective Equipment for Firefighters	: Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

5. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see chapter 8 of this Material Safety Data Sheet. See chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective measures	: Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Clean Up Method	: Slippery when split. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or Containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of property.
Additional Advice	: Local authorities should be advised if significant spillages cannot be contained.

6. HANDLING AND

STORAGE General	: Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Precautions	: Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists.
Handling	

	When handling product in drums, safety footwear should be worn and proper handling equipments should be used.
Storage	: Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage temperature : 0 - 50 C / 32 - 122 F.
Recommended Materials	: For containers or container linings, use mild steel or high density polyethylene.
Unsuitable Materials	: PVC
Additional Information	: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

7. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA(Mist.)		5 mg/m3	
Oil mist, mineral	ACGIH	STEL(Mist.)		10 mg/m3	

Exposure Controls	: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include : Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
Personal Protective Equipment	: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Respiratory Protection	: No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practises, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 C (149 F)]
Hand Protection	: Where hand contact with the product may occur the use of gloves approved to relevant standards (eg. Europe : EN374, US : F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.
Eye Protection	: Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	: Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Environmental Exposure	: Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

8. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Clear. Liquid at room temperature.
Odour	: Slight hydrocarbon.
pH	: Not applicable.
Initial Boiling Point and Boiling Range	: >280 C / 536 F estimated value (s)
Pour Point	: Typical -9 C / 16 F
Flash Point	: Typical 290 C / 554 F (COC)
Upper/Lower Flammability	: Typical 1 - 10% (V) (based on mineral oil)

or Explosion limits	
Auto-ignition temperature	: > 320 C / 608 F
Vapour Pressure	< 0.5 Pa at 20 C/68 F (estimated value(s))
Specific gravity	Typical 0.895 at 15 C / 59 F
Density	: Typical 895 g/cm ³ at 15 C / 59 F
Water Solubility	: Negligible
n-octanol/water partition coefficient (log power)	: >6 (based on information on similar products)
Kinematic viscosity (air=1)	: >1 (estimated value(s))
Vapour density (nBuAc=1)	: Data not available

9. STABILITY AND REACTIVITY

Stability	: Stable
Conditions to Avoid	: Extremes of temperature and direct sunlight.
Materials to Avoid	: Strong oxidising agents.
Hazardous Decomposition Products	: Hazardous decomposition products are not expected to form during normal storage.

10. TOXICOLOGICAL INFORMATION

Basis for Assessment	: Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity	: Expected to be of low toxicity : LD50 > 5000 mg/kg, Rat
Acute Dermal Toxicity	: Expected to be of low toxicity : LD50 > 5000 mg/kg, Rabbit
Acute Inhalation Toxicity	: Not considered to be an inhalation hazard under normal conditions of use.
Skin Irritation	: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Irritation	: Expected to be slightly irritating.
Respiratory Irritation	: Inhalation of vapours or mists may cause irritation.
Sensitisation	: Not expected to be a skin sensitiser.
Repeated Dose Toxicity	: Not expected to be a hazard.
Mutagenicity	: Not considered a mutagenic hazard.
Carcinogenicity	: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
Reproductive and Development Toxicity	: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Additional Information	

11. ECOLOGICAL INFORMATION

Ecotoxicology data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity	: Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic : LL/EL/IL50 > 100 mg/l (to aquatic organisms at concentrations less than 1mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1mg/l.
Mobility	: Liquid under most environmental conditions. Floats on water. If it enters soil. It will absorb to soil particles and will not be mobile.
Persistence/degradability	: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	: Contains components with the potential to bioaccumulate.
Other Adverse effect	: Product is a mixture of non-volatile components, which are not expected to be released

to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

12. DISPOSAL CONSIDERATIONS

Material Disposal	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment in drains or in water courses.
Container Disposal	: Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence collector or contractor should be established beforehand.
Local Legislation	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

13. TRANSPORT INFORMATION

US Department of Transportation Classification (49CFR)

This material is not subject to DOT regulations under 49 CFR Parts 171-180

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

14. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Notification Status

EINECS	All components listed or polymer exempt.
TSCA	All components listed.
DSL	All components listed.

SARA Hazard Categories (311/312)

No SARA 311/312 Hazards.

15. OTHER INFORMATION

	: 0,1,0
NFPA Rating (Health, Fire, Reactivity)	: 1.1
MSDS Version Number	: 20.12.2018
MSDS Effective Date	

MSDS Distribution	: The information in this document should be made available to all who may handle the product.
Disclaimer	: The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.