



## OnNix® COOLANT ANTIFREEZE 100%

*HIGH PERFORMANCE LONG-LIFE*

### Product Description

OnNix® high performance long-life coolant is blended from the finest quality mono ethylene glycol (MEG) and specialty additives. ONNIX 100% coolant must be diluted with distilled/de-ionized water prior to use. It is recommended for gasoline, diesel and natural gas powered vehicles. Perfect for mixed fleet applications. It provides excellent protection to radiator systems and is formulated to prevent corrosion to cooling systems. Suitable for use both in low and high temperatures. This product can be used down to -36°C and up to 125°C to prevent freezing in cold or overheating in hot temperatures.

### Dilution

Under normal mild weather conditions it is recommended to dilute the coolant to a 50% coolant to 50% distilled/de-ionized water ratio. Under severe cold weather conditions dilution can be reduced to a maximum of 70% coolant to 30% distilled/de-ionized water.

FEATURES	ADVANTAGES & POTENTIAL BENEFITS
MONO ETHYLENE GLYCOL, ANTIFOAM & ANTICORROSIVE	EXCELLENT ANTI-BOIL, ANTI-FREEZE QUALITIES. SUPERIOR CORROSION PREVENTION AND ANTI-FOAM PROTECTION.

### RECOMMENDATIONS & PRODUCT

#### PERFORMANCE CLAIMS

ONNIX HIGH PERFORMANCE LONG-LIFE COOLANT	FOR GASOLINE, DIESEL AND NATURAL GAS-POWERED VEHICLES EXCELLENT FOR MIXED FLEET APPLICATIONS.
MEETS	Chrysler MS 9176 Cummins 85T8-2 & 90T8-4 Ford ESE M97B49-A, WSS-M97B44-D & ESD M97 B49-A GM 6277M, W3420 John Deere H 24 B1 & C1 Leyland Trucks LTS 22AF 10 Mack 014GS 17004 MAN 248, 324 (SNF) & B&W D 36 5600 Mercedes MB 325.3 Renault 41-01-001 VAG TL 774F VOLVO

## Caution

This product is unlikely to produce any health hazards when used for its intended use and according to its usage instructions. Long term contact with skin may cause skin irritation or rashes. Wash off immediately with soap and water. Repeat till clean. Should irritation persist, see your doctor immediately. Keep away from eyes and do not swallow. Seek medical treatment immediately if ingestion occurs.



Protect the Environment - Dispose of used materials responsibly. Do not discharge into drains, soil or water.

TEST	BS COOLANT	SPECIFICATION LIMIT	METHOD
Appearance	CLEAR LIQUID	CLEAR LIQUID	VISUAL
COLOUR	OPTIONAL	OPTIONAL	VISUAL
DENSITY 20°C,	1.131 TYP		ASTM D5931
FREEZING POINT, °C (50 vol %)	( -33.8 TYP )		ASTM D1177
EQUILIBRIUM BOILONG POINT , °C	155 TYP	( > 150 )	ASTM D1120
RESERVE ALKALINITY	6 TYP	( > 3.0 )	ASTM D1121
PH	8.4 TYP	( 7 - 9.5 )	ASTM D1287