



OnNix® EP GEAR OIL

*Transmission GL-5***Premium Formulation**

OnNix® Premium Formulation Automotive Gear Oil is an extreme pressure (EP) gear lubricant that helps protect against severe temperatures, containing multi-functional additives required for mild extreme pressure conditions.

**Performance Benefits**

- Contains additives to inhibit oil oxidation and lubricated parts clean.
- Contains inhibitors to protect against corrosion, rust and foaming.

**Applications**

- Manual gear boxes of passenger cars and commercial vehicles operating under high speed/low torque and low speed/high torque conditions. Rear axles, suitable for applications presenting conditions of medium severity, such as light duty commercial vehicles and passenger cars. Not suitable for heavy duty hypoid axles.

**Recommended Specifications:**

- API Service Classification GL-5
- ZF-TE-MLO5A/07A/08A/12E/16D
- ZF TE-ML C-D
- ZF TE-ML 17B/19B/21B
- Scania STO 1:0
- Volvo 1273. 12
- MAN342N
- AGMA 9005-E02
- AGMA 9005-D94 ASIT 224
- AISE 224
- DAVID BROWN S1.53.101
- DIN 51517 PART3
- US STEEL 224
- FORD WSP-M2C197-A
- MERITOR 076-A/D/Q
- CINCINNATI MACHINE
- SAE J2360

## OnNix® EP GEAR OIL

SAE viscosity grade	EP 80W90	EP 85W140
Kinematic viscosity at 40°C (cSt)	140.5	380
Kinematic viscosity at 100°C (cSt)	14.9	28.4
Density at 15°C	0.887	0.908
Flash point, °C	212	227
Pour point, °C	-27	-12
Viscosity Index	104	99



Protect the Environment - Dispose of used materials responsibly. Do not discharge into drains, soil or water.