



OnNix® Fully Synthetic RS 0W30

Premium Performance

Product Description

OnNix® 0W30 SN/CF is an advanced fully synthetic engine oil designed to deliver outstanding engine protection, performance and enhanced fuel economy. Blended from the most advanced top tier additives available today at peak optimal levels and the highest quality fully synthetic base stocks. OnNix® 0W30 SN/CF has been formulated to meet the most stringent requirements of automotive manufacturers today.

Performance Benefits

Developed and blended using the best, selected fully synthetic base stocks and further fortified using top-tier synthetic additives, this product demonstrates excellent thermal and oxidative stability therefore allowing the product a longer service life, while maintaining the protective qualities of the oil throughout its service interval.

Advanced Additive Package / Lower Viscosity Lower Friction

This medium lower viscosity has been developed to deliver better fuel economy and excellent acceleration giving the driver a better total overall experience. The additive package API SN/CF bring a high level of detergency and dispersants to control carbon/sludge formation and to keep harmless in suspension any carbon particulate matter to keep engines clean and functioning at peak capacity for longer. The optimal level of detergents also helps in cleaning deposits left by inferior oils.

Premium Quality Multigrade/ Excellent Cold Weather Pumpability

This multigrade viscosity engine oil ensures a stable viscosity over a wider temperature range and the low winter grade ensures quick adequate lubrication even under cold temperatures for faster protection. This extends the engines overall lifespan.

Application

Specifically designed for gasoline engines. Recommended for vehicles requiring 0W30 viscosities and API SN/CF performance grades. Can be safely used in vehicles requiring 5W30, 10W30 viscosities.

Recommended Specifications::

- API SN PLUS / CF
- ACEA C2-16,C3-16

- MB Approval 229.52 , MB 229.51, MB229.31
- PORSCHE C30
- Renault RN0700, RN0710
- VW 504.00/507.00
- FIAT 955535.GS1, 955535.DS1

OnNix® Fully Synthetic Engine Oil RS 0W30

SAE viscosity grade		0W30
Kinematic viscosity at 40°C (cSt)	ASTM D445	67
Kinematic viscosity at 100°C (cSt)	ASTM D445	12.1
Density at 15°C	ASTM D4052	835.2
Flash point, °C	ASTM D92	226
Pour point, °C	ASTM D97	-54
Viscosity Index	ASTM D2270	175



Protect the Environment - Dispose of used materials responsibly. Do not discharge into drains, soil or water.